



Elite[®] gas furnaces come appointed with:

Insulated blower compartment to minimize heat loss and maximize efficiency

Designed to integrate with the PureAir[™] air purification system

Sturdy burners reduce noise and maintain efficiency throughout the unit life

Patented clamshell design reduces air leakage from the unit, sending more heated air to the home

Additional design elements, like pre-cut holes, pre-bent flanges and factory installed flue collars, make the installation quicker and more precise

Dual-fuel compatible with Lennox[®] heat pumps for added cost savings

	High-Efficiency, Fully Digital, Two-Stage, Variable-Speed Gas Furnace EL297V	High-Efficiency Two-Stage, Variable-Speed Gas Furnace EL296V	High-Efficiency Two-Stage, Constant-Torque Gas Furnace EL296E	High-Efficiency Single-Stage, Constant-Torque Gas Furnace EL196E	Standard-Efficiency Two-Stage, Constant-Torque Gas Furnace EL280E
Annual Fuel Utilization Efficiency (AFUE)	97%	96%	96%	96%	80%
Heat Stages	Two-Stage	Two-Stage	Two-Stage	Single-Stage	Two-Stage
Blower Motor	High-Efficiency Variable-Speed	High-Efficiency Variable-Speed	Power Saver Constant-Torque	Power Saver Constant-Torque	Power Saver Constant-Torque
ENERGY STAR [®] Certified ⁶	✓	✓	✓	✓	
Duralok Plus [™] Heat Exchanger	✓	✓	✓	✓	
Duralok [™] Heat Exchanger					✓
Fully Digital	✓	✓			
Enhanced Humidity Control	✓	✓			
Heat Exchanger Limited Warranty ³	Lifetime	Lifetime	Lifetime	Lifetime	20-Year
5-Year Limited Warranty On Covered Components ⁸	✓	✓	✓	✓	✓

Contact your local utility company to determine if there are available rebates.

For a full list of product details and testing, visit www.lennox.com/terms-and-conditions.
California Only: These furnaces do not meet the South Coast Air Quality Management District (SCAQMD) Rule 1111 NOx emission limit or the San Joaquin Valley Air Pollution Control District (SJVAPCD) NOx emission limit. For more details, visit www.lennox.com/terms-and-conditions.

www.lennox.com 1-800-9-LENNOX

For a complete list of the registered and common law trademarks owned by Lennox Industries Inc., please visit www.lennox.com.
 © 2023 Lennox Industries Inc. 19LNx0076 08/23 (20B08)

Annual Fuel Utilization Efficiency (AFUE)

Determines your furnace's fuel efficiency. The higher the AFUE, the more energy-efficient it is.

Fully Digital

A truly digital product is designed to pair with the Lennox S40 Smart Thermostat as part of a fully communicating home comfort system. Sensors in the equipment allow the thermostat to diagnose issues and automatically make system adjustments to more accurately and efficiently maintain temperature, humidity and air quality.

Power Saver™ Constant-Torque Blower Motor

A quieter upgrade over permanent split capacitor motors that offer greater comfort and 33% more efficiency.

Variable-Speed Blower Motor

The most efficient blower motor available with the ability to slowly ramp the airflow up or down to provide consistently even temperatures as it only produces the necessary amount of airflow at any given time.

ENERGY STAR® Certified

HVAC equipment with the ENERGY STAR label meets or exceeds federal guidelines for energy-efficient performance.

Duralok

A heat exchanger built for Lennox' mid-efficiency (80%) condensing gas furnaces that's made of high-quality heavy gauge aluminized steel to ensure high reliability and efficiency.

Duralok Plus

A heat exchanger built for Lennox' high-efficiency (90%) condensing gas furnaces that's made of high-quality heavy gauge aluminized steel to ensure high reliability and efficiency.

Dual-Fuel Compatibility

An HVAC system that pairs an electric heat pump with a gas furnace and alternates between the two fuel sources to maximize comfort and efficiency.

Warranty Your Way™

All Elite models come with a 10-Year Limited Warranty on compressors and a 5-Year Limited Warranty on covered components. A 10-Year Extended Limited Warranty is available with product registration. Furnace heat exchangers offer either 20-Year or Lifetime Limited Warranties. For more information, visit www.Lennox.com/WarrantyYourWay.

How does single-stage, two-stage & variable-capacity work?



72°

Single-Stage

Unit is either on or off, creating wide temperature swings.



72°

Two-Stage

Unit runs at either low or high speed, using the lower speed 80% of the time.



72°

Variable-Capacity

Unit runs at low most of the time, using only the amount of energy necessary to meet comfort need.

